

Danhydra grease pumps

Working at heights makes tool handling another challenge – Danhydra has developed this small, handy grease pump that elegantly combines light weight and easy handling with high performance.

A perfect solution for uncomplicated greasing of WTG bearings and central lubrication systems.

The automated filling sequence enables you to spend your time efficiently. Simply attach the tubes, specify the amount of grease you would like to add and let the pump do the rest, while you work on other tasks.



Benefits

- Automatic filling feature
- Provides accurate amount of grease
- Light weight
- Easy to operate and handle
- Compatible with any kind of grease
- Designed for standard grease cartridges

High pressure grease pump specs

Suitable for direct injection into mainly bearings. A flow divider can be used if you have multiple filling points.

- Maximum pressure: 250 bar
- Adjustable flow: up to 170 gr / min
- Weight: 12 kg
- Dimensions mm: H320 / W410 / D210
- Energy supply: 110V / 230V

High volume grease pump specs

Suitable for fast filling of auto lubrication containers, that are place by most WTG main components.

- Maximum pressure: 125 bar
- Adjustable flow: up to 250 gr / min
- Weight: 12 kg
- Dimensions mm: H320 / W410 / D210
- Energy supply: 110V / 230V

Danhydra grease filling

Danhydra can fill various sizes of cartridges with any type of grease, depending on your needs. We operate and manage our own in-house grease filling production.

We can also deliver your cartridges as white-label products, ready for you to rebrand with your own company name.

Our production takes place in a clinically clean environment, ensuring you high safety standards and quality. We have a production capacity of 500kg/hour, and offer to pack according to your requirements.

Our standard cartridge sizes are 1.5, 3 and 5 kg. Other sizes can be manufactured upon request.

Benefits

- Clinically clean filling environments
- Batch number traceability on each cartridge
- Packed according to your requirements
- Possibility to be packed at our 3 locations (Denmark, Germany & USA)

Data

- Standard cartridge sizes: 1,5 kg – 3 kg – 5 kg
- Production capacity: 500 kg / hour

